

LISTING OF THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. - 20. (Canceled)

21. (Previously Presented) A receiver circuit for providing a decoded output from a received discrete multi-tone modulated input signal, the input signal being received from a communication channel having noise thereon, the input signal comprising digital data, the circuit comprising:

a first stage having a frequency response for applying a discrete Fourier transform to the input signal; and

a second stage for receiving an output signal from said first stage and per-bin decoding said signal based on a maximum likelihood sequence estimation (MLSE) algorithm so as to recover said digital data;

wherein said maximum likelihood sequence estimation (MLSE) algorithm includes a calculation of state metrics and is modified to include subtraction of estimated noise samples using noise prediction coefficients.

22. (Original) The circuit of claim 21, wherein said noise prediction coefficients are the same for all bins.

23. (Original) The circuit of claim 21, wherein at least two bins or groups of bins have different respective noise prediction coefficients.

24. (Original) The circuit of claim 21, wherein said modified MLSE algorithm performs cancellation of noise received with said input signal from said communication channel.

25. (Original) The circuit of claim 24, wherein said noise is additive noise, additionally colored by a windowing procedure.

26. (Original) The circuit of claim 25, wherein said windowing procedure is time domain windowing.

27. (Original) The circuit of claim 25, wherein said windowing procedure is frequency domain windowing.

28. - 43. (Canceled)

44. (Original) A method in a receiver circuit for providing a decoded output from a received discrete multi-tone modulated input signal, the input signal being received from a communication channel having noise thereon, the input signal comprising digital data, the method comprising the steps of:

applying a discrete Fourier transform to the input signal; and then
per-bin decoding said signal based on a maximum likelihood sequence estimation algorithm so as to recover said digital data;

wherein said maximum likelihood sequence estimation (MLSE) algorithm includes a calculation of state metrics and is modified to include subtraction of estimated noise samples using noise prediction coefficients.

45. (Original) The method of claim 44, wherein said noise prediction coefficients are the same for all bins.

46. (Original) The method of claim 44, wherein at least two bins or groups of bins have different respective noise prediction coefficients.

47. (Original) The method of claim 44, further comprising the step of utilizing said modified MLSE algorithm to perform cancellation of noise received with said input signal from said communication channel.

48. (Original) The method of claim 47, wherein said noise is additive noise, additionally colored by a windowing procedure.

49. (Original) The method of claim 48, wherein said windowing procedure applies time domain windowing.

50. (Original) The method of claim 48, wherein said windowing procedure applies frequency domain windowing.